US 20190064472A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2019/0064472 A1**

Ishibashi (43) **Pub. Date: Feb. 28, 2019**

(54) **OPTICAL SYSTEM AND OPTICAL APPARATUS INCLUDING SAME**

(71) Applicant: **CANON KABUSHIKI KAISHA**, Tokyo (JP)

(72) Inventor: **Tomohiko Ishibashi**, Utsunomiya-shi (JP)

(21) Appl. No.: **16/114,321**

(22) Filed: **Aug. 28, 2018**

(30) **Foreign Application Priority Data**

Aug. 31, 2017 (JP) 2017-167283

Publication Classification

(51) **Int. Cl.**

G02B 7/02	(2006.01)
G02B 27/00	(2006.01)
G02B 7/10	(2006.01)
H04N 5/374	(2006.01)

(52) **U.S. Cl.**

CPC ***G02B 7/021*** (2013.01); ***H04N 5/374*** (2013.01); ***G02B 7/10*** (2013.01); ***G02B 27/0037*** (2013.01)

(57) **ABSTRACT**

An optical system of the present invention includes a plurality of lenses inclusive of an aspheric lens having an aspheric surface. A light absorption portion having thickness distribution in a direction perpendicular to an optical axis of the optical system is provided on the optical axis. Here, a refractive index of the aspheric lens, a refractive index of the light absorption portion, an aspheric sag amount of the aspheric lens, an aspheric sag amount of the light absorption portion, a height of a position in the aspheric lens through which a marginal ray of an axial ray passes, and a height of a position in the light absorption portion through which the marginal ray of the axial ray passes are each appropriately set.